
AirFRONT v7 aircuve Network (Wi-Fi) Access Authentication

Authentication and wireless segment encryption support



International Certification / Security Standard

Captive Portal



- IEEE802.1x auth standard support
- IEEE802.11i security standard support
- Wireless LAN encryption support (WPA1,2, WPA3)
- Standard RADIUS Protocol (IPv6, AAA standard support)
- Combined Auth (ID/PW+MAC) support
- ID based, MAC based, Authentication based support
- Ability to create multiple auth page support
- Employee/Guest auth page identity management function support
- Terminal Management function support
- Security protocol setting support
- WIPS interlock function support
- Guide statement setting function support
- Randomized MAC Address guide page support

SDN policy-based IP Mobility Integrated Auth Support



SDN policy-based IP Mobility Auth System support

- IP identity system for wired/wireless/smart terminals • User, ID, IP, MAC etc.. terminal integration management support
- Access control for user and terminal distinction support
- Auto registration support (minimum admin intervention)
- Agentless based & DHCP(important IP, IP protection) support
- Additional auth system for web terminal

AirFRONT v7 Certifications



- IITSCC CC certification [NISS-1138-2021]
- Wireless LAN security requirement V3.0R1
- Server security requirement V3.0R1
- Endpoint requirement V3.0
- EAL-Grade 4
- TTA Software Quality certificate [21-0428] - Grade 1 ...
- ISO 9001 Quality Management System certified

. .

AirFRONT v7



Product Config



Standard Server Spec

- CPUQuad-Core 3.4GHzHDD500GB SATA (2EA)
- NIC Gigabit (4Port)
- RAM 16GB
- SIZE 1U (43x439x548/mm)
- PSU Redundant Power
 - Power : 180W
 - Ampere : 0.8
 - Heat : 443
 - Single phase 3 line system



Product Spec

		Model	License	Item ID number
Public Procurement Service https://digitalmall.g2b.go.kr	AirFRONT v7	AirFRONT G1k	Simultaneous Connection 1,000	24458302
		AirFRONT G2k	Simultaneous Connection 2,000	24458303
		AirFRONT G3k	Simultaneous Connection 3,000	24458304
		DHCP Module	Max 3,000	24458301
		1 User License	1 License Add	24458300

Config

